

			Wood	Mineral
Total thickness	EN 428	mm	9.50	
Thickness of the wear-layer	EN 429	mm	0.35	
Weight / Mass per unit area	EN 430	g/sqm	7970	
Dimensions	EN 427	cm	129 x 19	119.8 x 27.2
Edges of planks	-	-	V Style / 4 bevelled edges	Straight edges
Surface treatment	-	-	Pureclean	
Embossing	-	-	wood grain	all over grain
Packaging	-	-	6 planks = 1.47 m ²	4 planks = 1.30 m ²
Norm / Product specification			EN 14085	
European classification	EN 685	class	23/32	
Fire rating - Classification	EN 13501-1	class	Bfl-s1	
Wear group	EN 653	group	T	
VOC rate (French norm)	-	-	A	
TVOC rate 28 days	-	µg/m ³	< 100	
Impact sound insulation	EN ISO 717/2	dB	18	
Room impact noise	NF S 31074	class	B	
Slip resistance wet: ramp test with oil	DIN 51 130	class	R10	
Colour fastness	EN 20 105-B02	degree	> 6	
Wet rooms	-	-	NO	
Floor heating	-	-	OK - T < 28°C	
Guarantee residential use	-	year	15	
Guarantee commercial use	-	year	5	

CE MARKING



Areas of use: domestic use

